

# C&M DURAFLEX™ PVC CENTRALIZERS

## Size Chart

Centralizer class/schedule is determined by the anchor's weight, angle of anchor installation and diameter of the drill hole or casing. The i.d. required is determined by the anchor o.d. The formed diameter of the centralizer is determined by the drill hole or casing i.d.

NOMINAL PIPE SIZE (in inches)	PIPE ID	MAIN WALL THICKNESS	FORMED DIAMETER	
			Minimum OD	Maximum OD

### CLASS 200 PVC

0.75	.926	.062	2	4
1.00	1.189	.063	2	5
1.25	1.502	.078	2	6
1.50	1.720	.090	3	8
2.00	2.149	.113	3	10
2.50	2.601	.137	4	12
3.00	3.166	.167	5	18
4.00	4.072	.214	5.5	24

### SCHEDULE 40 PVC

0.75	.824	.113	2	6
1.00	1.049	.133	2	10
1.25	1.380	.140	2.5	12
1.50	1.610	.145	3	16
2.00	2.067	.154	3.5	18
2.50	2.469	.203	4.5	20
3.00	3.068	.216	5	36
4.00	4.086	.237	5.5	36

### SCHEDULE 80 PVC

1.00	1.097	.179	3	10
1.25	1.278	.191	5	12
1.50	1.500	.200	5	16
2.00	1.939	.154	5	30
2.50	2.323	.276	5	30
3.00	2.900	.300	6	36
4.00	3.820	.337	7	36